

ORLEANS COUNTY FAIR, BARTON, VT - DEMO RULES
ANY QUESTION CALL DICK THERRIEN 802-274-8823
ABSOLUTELY NO CALLS BEFORE 8AM OR AFTER 8PM

NEW RULES FOR THE 2020 SEASON

- 1- ABSOLUTELY NO INTERIOR ROLL CAGES
- 2- SAFETY TECH INSPECTIONS ONLY PRE-RACE. SAFETY INSPECTORS MAY CHECK CERTAIN ITEMS OUTSIDE SAFETY ITEMS IF DEEMED NECESSARY.
 - 2A: WE WILL NO LONGER BE COMING TO YOU. YOU WILL COME TO US.
 - 2B: WHEN YOU PASS TECH YOU MUST GO STRAIGHT TO LINEUP AND CLOSE UP YOUR CAR THERE. NO GOING BACK TO PITS UNLESS YOU FAIL SAFETY TECH.
 - 2C: IF YOU FAIL SAFETY TECH, MAKE THE CORRECTION, RETURN TO TECH WITH THE SHEET & HAVE THE VEHICLE RECHECKED.
- 3- STOCK FUEL TANKS WILL BE ALLOWED IN THE BACK SEAT AREA OF DEMO VEHICLES
- 4- ALL CABIN MOUNTED FUEL TANKS & BATTERIES MUST BE UNCOVERED FOR TECH OFFICIALS TO INSPECT
- 5- YOU MUST USE 4 STEEL STRAPS TO SECURE YOUR FUEL TANK. 2 STRAPS REQUIRED FROM SIDE TO SIDE AND 2 FRONT TO REAR.
- 6- FRONT & REAR BUMPERS:
 - 6A: ANY ONE O.E.M. FRONT BUMPER ALLOWED ON THE FRONT
 - 6B: ANY ONE O.E.M. REAR BUMPER ALLOWED ON THE REAR.
 - 6C: NO FULL SIZE TRUCK BUMPERS ALLOWED ON CARS, MINI VANS OR COMPACT TRUCKS
 - 6D: NO HOMEMADE OR CUSTOM MADE BUMPERS OF ANY KIND.
 - 6E: BUMPERS WILL NOT BE WIDER THAN THE TRACK WIDTH OF THE TIRES
- 7- MANDATORY ALL DEMO CARS WILL HAVE A SEAT BACK SUPPORT. IT CAN BE MADE OF:
 - 7A- 2X2X 1/8 INCH THICK WALL HOLLOW SQUARE TUBE. YOU MAY WELD 2- 6X6X1/8 INCH THICK STEEL PLATES TO EACH END OF THE TUBE TO WELD TO THE "B" PILLARS
 - 7B- USE MINIMUM OF 1/4 INCH CHAIN RUN FROM "B" PILLAR TO "B" PILLAR OR
 - 7C- A MINIMUM OF FOUR INCH WIDE H.D. RATCHET STRAP RUN FROM "B" PILLAR TO "B" PILLAR
- 8- YOU MAY RUN A 2X2 HOLLOW SQUARE MAXIMUM 1/8 INCH THICK WALL TUBE FROM YOUR SEAT BACK RESTRAINT FORWARD TO A DASH SUPPORT OR FLOOR TO MOUNT YOUR SHIFTER, GAUGES, SWITCHES, ETC,
- 9- THE DRIVERS DOOR AND ONLY THE DRIVERS DOOR MUST BE PAINTED A FLEURESCENT COLOR. PASSENGER SIDE DOORS MUST BE REGULAR COLOR
- 10- NO FULL FRAMED CHRYSLER IMPERIALS ALLOWED. UNI-BODY CHRYSLER IMPERIALS ALLOWED